

Produits

Janus



Janus, the lightest and most compact crimp tool of its type, has a rotatable die set so that the ferrule can be inserted into the front or side of the tool to suit cabinet and bench working respectively. The tool is self-adjusting to produce a trapezoid shaped crimp profile on wire ferrules 0.14–10.0 mm²/AWG 26–8 (produced to DIN 46228-parts 1 and 4 or UL 486F).



Profil de sertissage

- Rotatable die set at the push of a button
- Self-adjusting die nest for 0.14–10.0 mm²/AWG 26–8 ferrules
- Trapezoid shaped crimp profile
- Compact design for easy access into constricted spaces
- Ergonomic handles and low handle force for low effort crimping
- Lightweight and well balanced
- Small handle opening angle
- Ratchet control (with emergency release) to ensure completion of crimp cycle
- Non-slip grip pad for applying pressure against a surface
- Hole in handle allows attachment of safety strap
- Each tool has a unique

DONNÉES TECHNIQUES

Longueur: 180 mm/7.09"

Largeur: 25 mm/0.98"

Hauteur: 65 mm/2.56"

Poids: 300 gr/0.66 lb

Calibre de fil: 0.14-10 mm² / AWG 26-AWG 8

Dimensions de sertissage mm/mm²

:

0,14 - 10,00

Dimensions de sertissage

inch/AWG:

26-8

Durée de vie en cycles: 50,000