


Product

KRB 0115S



KRB-0115S is a crimping tool for non insulated open barrel connectors, 2.8 + 4.8 mm, 0.1 - 1.5 mm²/.110" + .187", AWG 26-16, B/F-Crimp.

- High strength, through hardened alloy steel construction
- Unique mechanism significantly reduces hand force requirement over competing crimping tools
- Versatile and easy to customize for right hand or left hand users.
- Non-slip pad holds tool in place when leveraging on a work surface
- Full cycle crimp mechanism to ensure consistent, reliable crimp
- Ratchet release mechanism to clear miscrimps and obstructions
- Precision eccentric adjustment for consistent performance and ability to calibrate
- Hole in handle allows attachment of safety strap
- Each tool has a unique serial number for traceability



Die profile



Crimp profile

TECHNICAL DATA

Length: 204 mm/8.03"

Width: 22 mm/0.87"

Height: 76 mm/2.99"

Weight: 560 gr/1.23 lb

Wire size: 0.1-1.5 mm² / AWG 26-AWG 16

Crimp dimensions mm/mm²:
0,1 - 0,5 mm²/0,5 - 1 mm²/0,5 - 1,5 mm²

Crimp dimensions inch/AWG:
AWG 26 - 20/AWG 20 - 18/AWG 20 - 16

Connector: Uninsulated open barrel connectors

Description: For uninsulated open barrel connectors.

Life span, cycles: 50,000